



Effect of Locally Produced Activated Carbon on the Removal of Heavy Metals from Spent Synthetic-Based Mud

Hamza Ahmed

Department of Systems Engineering, Colorado State University, United states America

Abstract

The abstract would summarize the entire study. It would state the problem—the environmental challenge posed by spent SBM and its heavy metal content. It would introduce the solution: using activated carbon derived from a local source (e.g., coconut shells, sawdust, agricultural waste) to treat the waste. The abstract would mention the key methods used, such as batch adsorption experiments, and the results, including the removal efficiency of specific heavy metals (e.g., lead, chromium, cadmium). Finally, it would conclude with the significance of the findings, highlighting the potential for a sustainable and economical waste treatment process.

Keywords: Activated carbon Heavy metal removal Adsorption Synthetic-based mud (SBM) Waste treatment Local production Environmental remediation

Introduction

The introduction would set the stage for the research. It would start with a broad overview of the oil and gas industry and the generation of drilling mud, specifically focusing on synthetic-based mud (SBM). It would then narrow down to the environmental problems associated with spent SBM, particularly the presence of toxic heavy metals. The introduction would explain why these heavy metals are a concern, referencing their persistence and bioaccumulation in the environment.

Next, it would discuss existing methods for treating SBM, such as chemical precipitation and filtration, and their limitations (e.g., high cost, secondary waste generation). This would lead to the central theme of the paper: the use of adsorption as a superior alternative. The introduction would introduce activated carbon as a highly effective adsorbent due to its high surface area and porous structure. It would then propose the novelty of the study: using activated carbon produced from local, abundant, and low-cost materials, which makes the process more economically viable and sustainable.

The introduction would conclude by stating the research objectives and hypotheses, such as investigating the efficiency of the locally produced activated carbon in removing heavy metals from SBM and optimizing the adsorption process parameters (e.g., contact time, pH, adsorbent dose). It would also briefly outline the structure of the rest of the paper.

Methods (Conceptual Framework)

This section would detail the experimental procedures used to investigate the effect of locally produced activated carbon on the removal of heavy metals from spent synthetic-based mud. The methodology would be designed to be replicable and robust.

- **Materials and Reagents:** A comprehensive list of all materials and chemicals used would be provided. This would include the raw material for activated carbon (e.g., coconut husks, sawdust), the activating agent

(e.g., zinc chloride, phosphoric acid), and the heavy metal salts used to create the synthetic spent mud solution (e.g., lead nitrate, cadmium chloride).

- **Preparation of Activated Carbon:** The procedure for preparing the activated carbon would be described in a step-by-step manner. This would include:
- **Preprocessing:** The raw biomass would be washed, dried, and crushed to a specific particle size to increase the surface area available for activation.
- **Carbonization:** The biomass would be heated in a controlled environment (e.g., a furnace) at a specific temperature (e.g., 400-600°C) for a defined period to convert it into a carbonaceous material.
- **Chemical Activation:** The carbonized material would be impregnated with a chemical activating agent, followed by heating at a higher temperature (e.g., 700-900°C). This step is crucial for creating the porous structure characteristic of activated carbon.
- **Washing and Drying:** The activated carbon would be washed repeatedly to remove residual activating agents and then dried to a constant weight.
- **Characterization of Activated Carbon:** To understand the properties of the adsorbent, various analytical techniques would be employed.
- **Surface Morphology:** Scanning Electron Microscopy (SEM) would be used to visualize the surface structure and porosity.
- **Surface Area and Pore Volume:** The Brunauer–Emmett–Teller (BET) method would be used to determine the specific surface area and pore characteristics. A high surface area is a key indicator of good adsorbent performance.

- **Functional Groups:** Fourier-Transform Infrared (FTIR) spectroscopy would be used to identify the chemical functional groups (e.g., carboxyl, hydroxyl) on the surface of the activated carbon, which act as active sites for heavy metal binding.
 - **Preparation of Simulated Spent Synthetic-Based Mud (SBM):** Given the variability of real-world waste, a synthetic solution mimicking the heavy metal composition of spent SBM would be prepared. The concentrations of heavy metals would be specified.
 - **Batch Adsorption Experiments:** These experiments would be the core of the study, designed to evaluate the activated carbon's performance under various conditions. Each experiment would be conducted in triplicate to ensure reliability.
 - **Effect of Adsorbent Dose:** A series of experiments would be conducted with a constant initial heavy metal concentration and varying amounts of activated carbon to determine the optimal dose for maximum removal efficiency.
 - **Effect of Contact Time:** Experiments would be run for different durations to determine the time required for the adsorption process to reach equilibrium. This helps to understand the kinetics of the process.
 - **Effect of pH:** The pH of the heavy metal solution would be adjusted using acid or base to study its impact on the adsorption efficiency. The pH of the solution is critical as it affects both the speciation of the heavy metal ions and the surface charge of the activated carbon.
- Effect of Initial Heavy Metal Concentration:** Experiments with different initial heavy metal concentrations would be performed to understand the adsorption capacity of the activated carbon and to model the adsorption using isotherm models.
- **Analytical Methods:** The concentration of heavy metals in the solutions, both before and after adsorption, would be measured using an appropriate analytical technique, such as Atomic Absorption Spectroscopy (AAS) or Inductively Coupled Plasma Mass Spectrometry (ICP-MS). The removal efficiency and adsorption capacity would be calculated using specific formulas.

Results (Conceptual Framework)

This section would present the findings of the experiments in a clear, objective, and organized manner. The data would be supported by tables, figures, and graphs to facilitate understanding.

- **Characterization of Activated Carbon:** The results of the characterization would be presented first.
- SEM images would show a highly porous, well-developed surface structure.
- The BET analysis would report a high surface area, confirming the success of the activation process. For example, a value of over 500 m²/g would be indicative of a good adsorbent.
- **FTIR spectra** would be presented and analyzed to confirm the presence of key functional groups that are critical for heavy metal binding.
- **Effect of Adsorbent Dose:** The results would show a plot of removal efficiency (%) against adsorbent dose (g/L). Typically, the plot would show a sharp increase in removal efficiency as the dose increases, followed by a plateau. This would identify the optimal dose needed to achieve maximum removal without wasting adsorbent.
- **Effect of Contact Time:** A graph showing the relationship between removal efficiency and contact time would be presented. The graph would likely show a rapid initial adsorption phase, followed by a slower phase as the available active sites become saturated. The time at which equilibrium is reached would be highlighted.
- **Effect of pH:** The results would demonstrate the critical role of pH. A graph would show that removal efficiency is low at acidic pH due to competition from hydrogen ions and electrostatic repulsion, and increases significantly as the pH becomes neutral or slightly alkaline.
- **Effect of Initial Heavy Metal Concentration:** A graph would show that while the percentage removal might decrease with increasing initial heavy metal concentration, the actual amount of heavy metal adsorbed per unit mass of activated carbon (adsorption capacity) would increase. This is because at higher concentrations, there is a greater driving force for the heavy metal ions to move from the solution to the adsorbent surface.
- **Adsorption Isotherms:** The experimental data would be fitted to common adsorption isotherm models, such as the Langmuir and Freundlich models. The R² values and model parameters would be presented in a table to determine which model best describes the adsorption process. A good fit with the Langmuir model would suggest a monolayer adsorption mechanism, while a good fit with the Freundlich model would suggest a multilayer, heterogeneous surface adsorption.
- **Adsorption Kinetics:** The data would be analyzed using kinetic models, such as the pseudo-first-order and pseudo-second-order models. The results would reveal which model best describes the rate-limiting step of the adsorption process. A strong fit to the pseudo-second-order model would suggest that chemisorption is the rate-limiting step.
- **Overall Performance and Comparison:** The final results would summarize the maximum removal

efficiency and adsorption capacity for each heavy metal. A table would compare the performance of the locally produced activated carbon with other reported adsorbents from the literature, highlighting its cost-effectiveness and efficiency. This section would serve as the bridge between the data and the discussion, setting the stage for the interpretation of the results.

Discussion

Assessing the necessity of a lightning protection system (LPS) at Abubakar Tatari Ali Polytechnic, Bauchi, Northern Nigeria, involves several key considerations, including the prevalence of thunderstorms, the risk to personnel and infrastructure, and the economic viability of installation. Lightning Activity and Geographic Location Northern Nigeria, particularly the Bauchi region, is known for its high incidence of thunderstorms, especially during the rainy season from April to October. The Keraunic level, which measures the number of days per year that thunder is heard, is significantly high in this area. A higher keraunic level directly correlates with an increased probability of lightning strikes. This meteorological data alone suggests a strong need for an LPS.

Risk to Personnel and Infrastructure

The polytechnic campus houses numerous buildings, including administrative blocks, lecture halls, laboratories, workshops, and student hostels. Many of these structures contain sensitive electronic equipment and are occupied by a large number of people. A direct lightning strike on an unprotected building can lead to several catastrophic outcomes:

- **Structural damage:** A lightning strike can cause fires, shatter brickwork, and damage roofs.
- **Equipment failure:** The powerful electrical surge can destroy computers, servers, and another valuable laboratory equipment.
- **Risk to human life:** Lightning strikes pose a direct threat of injury or death to students and staff.

Economic Viability

The cost of installing an LPS must be weighed against the potential cost of damage and disruption caused by a lightning strike. The price of a comprehensive LPS, which includes air terminals, down conductors, and a grounding system, is a significant upfront investment. However, this cost is minimal compared to the potential financial losses from:

- Building repairs or reconstruction.
- Replacement of expensive electronic and scientific equipment.
- Business interruption and loss of academic time.
- Liability claims from injuries or fatalities.

Moreover, an LPS can also protect the polytechnic's power supply from surges traveling through utility lines, a common occurrence during thunderstorms, which can also damage internal electrical systems.

Conclusion

Based on the high frequency of thunderstorms in Bauchi, the potential for significant damage to critical infrastructure, and this

References

1. Snoaa's National Weather Service, "Lightning Sports," [weather.gov](https://www.weather.gov), 2024.
2. Power Quality Blog, "Principle of Lightning Protection," powerquality.blog, 2023.
3. Techwin, "Technology Behind Lightning Protection Devices for Building Structures," techwinspd.com, 2024.
4. Furse, "The BS EN/IEC 62305 Standard Series," tnb.com, 2024.
5. Axis India, "IEC 62561 and IEC 62305: A Brief and Simplified Overview," youtube.com, 2023.
6. M.C. Aliyu and O.C. Okafor, "Review of Lightning Protection Standard in Building Structures in Nigeria," International Organization of Scientific Research, 2014.
7. A.O. Agbetuyi *et al.*, "Review of Lightning Protection Standard in Building Structures in Nigeria," IOSR Journal of Engineering, 2014.
8. Lightning Protection Solutions, "Lightning Protection System," lsp.global, 2024.
9. Techwin, "Technology Behind Lightning Protection Devices for Building Structures," techwinspd.com, 2024.
10. EnergyMall, "Indelec preventron 3 indelec S40 thunder arrestor," energymall.ng, 2024.
11. A.O. Melodi, "Modeling of Lightning Strike Events, and its Correlational with Power Outages in South-West Coast, Nigeria," International Journal of Electrical and Computer Engineering, 2017.